



TIMER MULTIMEDIA FILTER (2")

DESCRIPTION:

The automatic backwashing sediment filters utilize the Fleck 3150 brass valve, composite media tank, anthracite, quartz sand and garnet for long lasting depth filtration.

FEATURES:

- The control valve utilizes the time proven piston-seal-spacer technology for durable, maintenance free service.
- Plastic and brass construction will not corrode.
- Media bed has three layers selected for particle size and specific gravity providing highly efficient removal of particulate matter from water. The top layer traps coarse debris, the middle layer traps medium size particles, and the bottom layer traps particles as small as 10 microns.
- The multimedia design offers the advantage of efficient filtering and long service runs between filter backwashes.



Tank not shown

OPERATING REQUIREMENTS

Pressure	20-100 PSI
Temperature	35-100°F
Electrical	120V, 60 Hz, 5 amps
Turbidity	< 55 NTU

SPECIFICATIONS

Model	0096155	0096156	0096157	0096158
Continuous Flow Rate* GPM	28	44	63	86
Peak Flow Rate GPM	47	73	100	124
Media Cu. Ft.	10	15	20	30
Tank Size In.	24 x 72	30 x 72	36 x 72	42 x 72
Drain Flow GPM	35	50	75	100
Valve Pipe Size In.	2	2	2	2
Weight Lbs.	935	1,385	2,170	2,810

* Continuous flow rate based on 9 GPM per square foot for water less than 55 NTU. Slower rates should be used for higher NTU.