



POLYPROPYLENE SEDIMENT FILTER CARTRIDGES

SPUN-BONDED CARTRIDGES

DESCRIPTION:

The spun-bonded cartridges are manufactured from 100% polypropylene filters. The fibers have been carefully spun together to form a true gradient density from outer to inner surfaces.

They are designed for purity. The filters will not impart taste, odor, color or foam. Additionally, the construction provides superior chemical resistance and is not prone to bacterial attack.

Temperature Rating 40°F to 145°F.

SPECIFICATIONS					
Model (Each)	Micron Rating	Size In. (Dia. x L)	Initial Flow GPM*	Model (Case)	Quantity Per Case
20-1011	1 µm	2½ x 10	5	20-1011-24	24
20-1012	1 µm	2½ x 20	10	20-1012-20	20
20-1015	1 µm	4½ x 10	10	20-1015-8	8
20-1016	1 µm	4½ x 20	20	20-1016-6	6
20-1051	5 µm	2½ x 10	7	20-1051-24	24
20-1052	5 µm	2½ x 20	11	20-1052-20	20
20-1053	5 µm	2½ x 30	11	-----	-----
20-1055	5 µm	4½ x 10	11	20-1055-8	8
20-1056	5 µm	4½ x 20	22	20-1056-6	6

* Estimated on clean cartridges and less than 1 PSI pressure drop.



PLEATED CARTRIDGES

DESCRIPTION:

The pleated cartridges are manufactured from a special formulation of resin-impregnated cellulose and polyester fibers. This unique blend of materials provides a higher wet strength than regular cellulose cartridges. It also provides high flow rates and dirt holding capacity, while maintaining extremely low pressure drop.

Temperature Rating 40°F to 125°F.

SPECIFICATIONS					
Model (Each)	Micron Rating	Size In. (Dia. x L)	Initial Flow GPM*	Model (Case)	Quantity Per Case
20-2212	1 µm	4½ x 20	25	20-2212-6	6

* Estimated on clean cartridges and less than 1 PSI pressure drop.

