



SPUN-BONDED POLYPROPYLENE SEDIMENT FILTER CARTRIDGES

DESCRIPTION:

The spun-bonded cartridges are manufactured from 100% polypropylene filters. The fibers have been carefully spun together to form a true gradient density from outer to inner surfaces.

They are designed for purity. The filters will not impart taste, odor, color or foam. Additionally, the construction provides superior chemical resistance and is not prone to bacterial attack.

Temperature Rating 40°F to 145°F.



SPECIFICATIONS					
Model (Each)	Micron Rating	Size In. (Dia. x L)	Initial Flow GPM*	Model (Case)	Quantity Per Case
20-1011	1 µm	2½ x 10	5	20-1011-24	24
20-1012	1 µm	2½ x 20	10	20-1012-20	20
20-1015	1 µm	4½ x 10	10	20-1015-8	8
20-1016	1 µm	4½ x 20	20	20-1016-6	6
20-1051	5 µm	2½ x 10	7	20-1051-24	24
20-1052	5 µm	2½ x 20	11	20-1052-20	20
20-1055	5 µm	4½ x 10	11	20-1055-8	8
20-1056	5 µm	4½ x 20	22	20-1056-6	6

* Estimated on clean cartridges and less than 1 PSI pressure drop.